

ALI LED

LED area lighting for industrial locations

Accessories










Outlet Boxes	Catalog No.	Conduit Hub Size (in.)	Shipping Weight (lbs.)
Rigid Pendant 	SMP	3/4	3.3
	SMP1	1	3.3
Ceiling Mount 	SMC	3/4	4.1
	SMC1	1	4.1
Wall Mount 	SMW	3/4	7.8
	SMW1	1	7.8
25° Stanchion Mount 	SMS	1-1/4	5.9
	SMS1	1-1/2	5.9
90° Stanchion Mount 	SML	1-1/4	5.9
	SML1	1-1/2	5.9

Photo Cell Kit*	Catalog No.	Description	Shipping Weight (lbs.)
	SPH25-120	Automatic on-off switch at predetermined light levels. (120 volt only) REQUIRES FIELD INSTALLATION.	.19

* Not Suitable for hazardous locations.

SAF/SAFR Adapter Ring	Catalog No.	Description	Shipping Weight (lbs.)
	RTXMV	Adapter Ring UL listed as Luminaire Fitting for use in Class I Div. 2 Groups A, B, C & D and Marine. Mates with competitor models APM2, APM3, HPM2, CM2, CM3, TWM2, TWM3, JM5, PM5 and QM25 mounts	3.25

Guards / Safety Cable	Catalog No.	Description	Shipping Weight (lbs.)
	SXP10WG	Stainless Steel Wire Guard for Low Profile Clear and Frosted Globes	1.0
	10128R	Open fuse block kit - 600 volt AC maximum	1.0

Globe	Catalog No.	Description	Shipping Weight (lbs.)
	SGL10T	Low Profile Clear Glass Globe	4.2
	SPG10C	Low Profile Clear Polycarbonate Globe	2.5
	SFGL10T	Low Profile Frosted Glass Globe	4.2
	SPG10F	Low Profile Frosted Polycarbonate Globe	2.5



An Avail Infrastructure Solutions Company

availinfra.com/rig-a-lite

8500 Hansen Road,
Houston, TX 77075
(713) 943-0340

Fixtures ordered with refractors are not suitable to be ordered with reflectors.

Refer to Certification Guide to determine suitability of individual fixture.