







SAFR LED


LED area lighting for hazardous locations



Accessories

| Outlet Boxes | Catalog No. | Conduit Hub Size (in.) | Shipping Weight (lbs.) |
|---|-------------|------------------------|------------------------|
| Rigid Pendant  | SMP | 3/4 | 3.3 |
| | SMP1 | 1 | 3.3 |
| Ceiling Mount  | SMC | 3/4 | 4.1 |
| | SMC1 | 1 | 4.1 |
| Wall Mount  | SMW | 3/4 | 7.8 |
| | SMW1 | 1 | 7.8 |
| 25° Stanchion Mount  | SMS | 1-1/4 | 5.9 |
| | SMS1 | 1-1/2 | 5.9 |
| 90° Stanchion Mount  | SML | 1-1/4 | 5.9 |
| | SML1 | 1-1/2 | 5.9 |

| Hazardous Location Photo Cell Kit* | Catalog No. | Description | Shipping Weight (lbs.) |
|--|--------------|--|------------------------|
|  | HLPC-120 | Automatic on-off switch at predetermined light levels. (120 volt only) | .25 |
| | HLPC-208-277 | REQUIRES FIELD INSTALLATION. | .25 |

* Not Suitable for hazardous locations.

| SAF/SAFR Adapter Ring | Catalog No. | Description | Shipping Weight (lbs.) |
|--|-------------|--|------------------------|
|  | RTXMV | Adapter Ring UL listed as Luminaire Fitting for use in Class I Div. 2 Groups A, B, C & D and Marine. Mates with competitor models APM2, APM3, HPM2, CM2, CM3, TWM2, TWM3, JMS, PM5 and QM25 mounts | 3.25 |

| Guards / Safety Cable | Catalog No. | Description | Shipping Weight (lbs.) |
|---|-------------|---|------------------------|
|  | SXP10WG | Stainless Steel Wire Guard for Low Profile Clear and Frosted Globes | 1.0 |
|  | 10128R | Open fuse block kit - 600 volt AC maximum | 1.0 |

| Globe | Catalog No. | Description | Shipping Weight (lbs.) |
|--|-------------|---|------------------------|
|  | SGL10T | Low Profile Clear Glass Globe | 4.2 |
| | SPG10C | Low Profile Clear Polycarbonate Globe | 2.5 |
|  | SFGL10T | Low Profile Frosted Glass Globe | 4.2 |
| | SPG10F | Low Profile Frosted Polycarbonate Globe | 2.5 |



An Avail Infrastructure Solutions Company

availinfra.com/rig-a-lite

8500 Hansen Road,
Houston, TX 77075
(713) 943-0340

Fixtures ordered with refractors are not suitable to be ordered with reflectors.

Refer to Certification Guide to determine suitability of individual fixture.