

# Quickship Ordering

Quality lighting is essential for safety and productivity—downtime isn't an option. RIG-A-LITE's QuickShip ordering ensures fast access to our most popular products, helping you meet tight deadlines or quickly restore safe, efficient illumination. Many fixtures ship within 2 to 3 days (quantity limits apply).

To order, visit [availinfra.com/rig-a-lite-quickship](https://availinfra.com/rig-a-lite-quickship), complete the QuickShip Order form, and submit it.

## Qualifying Products

Model	Style	Wattage	Operating Voltage	Total Lumens	Lumens per Watt	CRI	CCT	Ambient Temperature
AVPH20L2UHFGC	Hazardous-rated globe and guard	20W	120V - 277 V 50/60 Hz	1769	87	83	4017	-20°C < Tamb <50°C
HZALJ08LUCGC	Hazardous-rated low-profile area light	53W		7561	142	81	4896	-40°C < Tamb <70°C
HZALJ08LUCGP	Hazardous-rated low-profile area light	53W		7561	142	81	4896	-40°C < Tamb <70°C
LHFLJ12LUTP76	Hazardous-rated floodlight/high-bay	98W		12919	131	71	4824	-40°C < Tamb <65°C
LHFLJ13LUTP76	Hazardous-rated floodlight/high-bay	119W		14121	119	71	4994	-40°C < Tamb <65°C
LHFLJ15LUTP76	Hazardous-rated floodlight/high-bay	132W		15359	116	72	4961	-40°C < Tamb <65°C
LHFL17LUTP76	Hazardous-rated floodlight/high-bay	127W		16420	129	75	4961	-40°C < Tamb <65°C
LHFL20LUTP76	Hazardous-rated floodlight/high-bay	164W		20239	124	72	5046	-40°C < Tamb <65°C
MHL07LC4URIG	Hazardous-rated linear, Safety Cbl / Mtg Brkt	52W		7261	140	83	4105	-35°C < Tamb <60°C
MHL07LC4UMB	Hazardous-rated linear, Mtg Brkt	52W		7261	140	83	4105	-35°C < Tamb <60°C
XML07LC4UMB	Explosion-proof linear, Mtg Brkt	54W		7291	134	82	4167	-40°C < Tamb <60°C
XML07LC4URIG	Explosion-proof linear, Safety Cbl / Mtg Brkt	54W		7291	134	82	4167	-40°C < Tamb <60°C



An Avail Infrastructure Solutions Company

[availinfra.com/rig-a-lite](https://availinfra.com/rig-a-lite)

8500 Hansen Road  
Houston, TX 77075  
(713) 943-0340