



LED Luminaires for Hazardous Locations

Installation and Operation Instructions



RIG-A-LITE
EX-SERIES

8500 Hansen Rd.
Houston, TX 77075 USA
Tel: (713) 943-0340
availinfra.com/rig-a-lite/



This product comply with below standard:

UL 50 UL 50E
UL 1598 UL 1598A
UL 8750 UL 844
UL 924
CSA/UL 60079-0
CSA/UL 60079-15
CSA/UL 60079-31
CSA C22.2 No. 94.1
CSA C22.2 No. 94.2
CSA C22.2 No. 137
CSA C22.2 NO. 141
CSA C22.2 No. 250.6

Certifications:


Class I, Division 2, Groups A, B, C, D
Class II, Division 2, Groups F, G
Class III
Ex nR IIC T6/T5 Gc
Ex tb IIIC T80°C/95°C Db
Zone 2, AEx nR IIC T6/T5 Gc
Zone 21, AEx tb IIIC T80°C/95°C Db
Simultaneous Presence
Suitable for Use Wet Locations
Suitable for Marine locations
Emergency Battery Back-up
Type 4X IP66

Typical application sites are: Oil and gas refineries, drilling rigs, petrochemical facilities, food and beverage facilities, p
latforms, loading docks, tunnels, indoor/outdoor spotlighting, outdoor wall and stanchion mounted general area lighting,
and where flammable vapors, gases, ignitable dusts, fibers or flyings are present.


Physical Dimensions (Flat glass) (Unit: mm/inch)

Power:30/40/50/60/75W


Ceiling Mount (1)




Ceiling Mount (2)




Pendant Mount




Trunnion Mount




Pendant & Trunnion Mount




Wall Bracket Mount




25° Stanchion Mount



30° Stanchion Mount




90° Stanchion Mount




Physical Dimensions (Curved glass) (Unit: mm/inch)

Power:30/40/50/60/75W


Ceiling Mount (1)




Ceiling Mount (2)




Pendant Mount




Trunnion Mount




Pendant & Trunnion Mount




Wall Bracket Mount




25° Stanchion Mount




30° Stanchion Mount




90° Stanchion Mount




Tools that may be used during installation




Adjustable wrench



Bayonet wrench



Bayonet wrench



Cross screwdriver


Accessory

Ceiling Mount 1



Dimension: 349x239x57mm
Surface Treatment: Powder coating
Code: MK-EXA10-02

Ceiling Mount 2




Dimension: 349x239x92mm
Surface Treatment: Powder coating
Code: MK-EXA10-01

Pendant Mount




Dimension: 276x276x88mm
Surface Treatment: Powder coating
Code: MK-EXA10-03

Trunnion Mount




Dimension: 268x239x186mm
Surface Treatment: Powder coating
Code: MK-EXA10-05

Pendant & Trunnion Mount



Dimension: 268x239x186mm
Surface Treatment: Powder coating
Code: MK-EXA10-04

Wall Bracket Mount



Dimension: 345x276x88mm
Surface Treatment: Powder coating
Code: MK-EXA10-06

25° Stanchion Mount




Dimension: 351x276x73.1mm
Surface Treatment: Powder coating
Code: MK-EXA10-07

30° Stanchion Mount




Dimension: 355.1x276x77.5mm
Surface Treatment: Powder coating
Code: MK-EXA10-08

90° Stanchion Mount



Dimension: 350.5x276x83mm
Surface Treatment: Powder coating
Code: MK-EXA10-09

Wire Guard




Dimension: 214.5x214.5x6mm
Surface Treatment: Powder coating
Code: BC-EXA10-01

Curved wire guard



Dimension: 214.5x214.5x102mm
Surface Treatment: Powder coating
Code: BC-EXA10-02

Safety cable



Buckle size: Ø4x40 mm
Cable length : 2m
Material : SUS304
Color: Natural color
Code: SL-EXA10-01

Cone Top



Dimension: 237.9x237.9x113.6mm
Surface Treatment: Powder coating
Code: AD-EXA10-01

Product Specifications

Power		30W	40W	50W	60W	75W
Input Voltage		120-277Vac / 277-480Vac, 50 / 60 Hz				
Outlook Dimensions	Ceiling Mount(1)	349x246x163mm(13.74"x9.68"x6.41") (Flat glass) / 349x246x268mm(13.74"x9.68"x10.55") (Curved glass)				
	Ceiling Mount(2)	349x246x198mm(13.74"x9.68"x7.79") (Flat glass) / 349x246x303mm(13.74"x9.68"x11.92") (Curved glass)				
	Pendant Mount	263x246x197mm(10.35"x9.68"x7.75") (Flat glass) / 263x246x299mm(10.35"x9.68"x11.77") (Curved glass)				
	Trunnion Mount	268x246x299mm(10.55"x9.68"x11.77") (Flat glass) / 268x246x404mm(10.55"x9.68"x15.90") (Curved glass)				
	Pendant&Trunnion Mount	268x246x299mm(10.55"x9.68"x11.77") (Flat glass) / 268x246x404mm(10.55"x9.68"x15.90") (Curved glass)				
	Wall Bracket	345x246x172mm(13.58"x9.68"x6.77") (Flat glass) / 345x246x277mm(13.58"x9.68"x10.90") (Curved glass)				
	25° Stanchion Mount	351x246x158mm(13.81"x9.68"x6.22") (Flat glass) / 351x246x263mm(13.81"x9.68"x10.35") (Curved glass)				
	30° Stanchion Mount	355.1x246x158mm(13.98"x9.68"x6.22") (Flat glass) / 355.1x246x263mm(13.98"x9.68"x10.35") (Curved glass)				
Luminaire Net Weight	90° Stanchion Mount	350.5x246x158mm(13.79"x9.68"x6.22") (Flat glass) / 350.5x246x263mm(13.79"x9.68"x10.35") (Curved glass)				
	Ceiling Mount(1)	4.2kg (9.26Lbs)(Flat glass) / 5.4kg (11.9Lbs)(curved glass)				
	Ceiling Mount(2)					
	Pendant Mount	3.9kg (8.6Lbs)(Flat glass) / 5.1kg (11.24Lbs)(curved glass)				
	Trunnion Mount					
	Pendant&Trunnion Mount	4.4kg (9.7Lbs)(Flat glass) / 5.6kg (12.35Lbs)(curved glass)				
	Wall Bracket	4.4kg (9.7Lbs)(Flat glass) / 5.6kg (12.35Lbs)(curved glass)				
	25° Stanchion Mount	4kg (8.82Lbs)(Flat glass) / 5.3kg (11.68Lbs)(curved glass)				
Emergency model	EM Wattage & EM time	9W 1.5h (Input Voltage: 120-277Vac, 50 / 60 Hz)				
	Battery Capacity	6.4V 3200mAh				
Working Temperature		-40°C to +65°C (-40°F to +149°F) (Only 30W/40W/50W) -40°C to +60°C (-40°F to +140°F) (Only 60W/75W) 0°C to +50°C (32°F to +122°F) (Only Emergency model 30W/40W) 0°C to +45°C (32°F to +113°F) (Only Emergency model 50W) 0°C to +40°C (32°F to +104°F) (Only Emergency model 60W/75W)				
Storing Temperature		-40°C to +70°C (-40°F to +158°F)				

* The tolerance for weight is ±6%.

Luminaire Shipping Packing List

Name	QTY
EXA10 Series Luminaire	1 pc
EXA10 Series Installation and operation instructions	1 pc

Model description

Model description:

EXA	Options: WG=Wire guard; EM=Emergency Battery; DM=Dimmable; ED=Emergency Battery & Dimmable AP=Adjustable Power; CT=Cone Top
10	Mounting Style: C=Ceiling mount; T=Trunnion Mount; P=Pendant Mount; M= Pendant & Trunnion Mount W=Wall Bracket; S=25° Stanchion Mount; X=30° Stanchion Mount; V=90° Stanchion Mount
-XXX-X-XX-XXX-XX-X-XX	Diffusion Material: CG=Flat clear glass; GG=Curved grille glass Beam Distribution: 000=120°(No lens); 020=T10701(Type I); 021=T10703(Type III) 022=T10706(60°); 023=T10707(90°)
-	CCT(K): 20=2000; ... ; 65=6500; Re=Red; Gr=Green; Bl=Blue; Am=Amber
-	Voltage: U=120-277Vac, 50/60Hz; V=277-480Vac, 50/60Hz
-	Lamp Wattage: 030=30W; 040=40W; 050=50W; 060=60W; 075=75W
-	Lamp Code: 10
-	Series constant: EXA-Hazardous

Installation and Operation Instructions



Dear Customers and Users:

Thank you very much for purchasing our product. In order to better understand how to use this product safely, please read this instruction patiently and carefully. And please keep the manual properly for future reference.


Warnings:


1. The product can be connected to a power supply of 120-277Vac 50/60Hz or 277-480Vac 50/60Hz as specified on the label on the product.
2. DO NOT dismantle, modify or replace any internal electronic components. If you have any confusion during installation, please contact local dealer or contact us directly.
3. Please be sure to turn off the power before installation, maintenance or any other actions that may touch the light.
4. DO NOT install the lights on the surface that is easy to be damaged and deformed.
5. Under no circumstances can this light be covered with thermal insulation or any other similar materials.
6. If emergency or abnormality occurs, please cut off the power firstly and contact your local dealer as soon as possible.
7. The product is suitable for both indoor and outdoor use. Please do not touch the light while it is working.
8. Any installation and maintenance must be performed by certified electricians only.
9. Do not open the enclosure when the light is working.
10. Do not use this luminaire on an ungrounded circuit, otherwise it can cause a fatal electric shock.
11. Do not look directly at the LEDs when energized.
12. For emergency lighting, replacement of battery packs is not allowed.
13. The product is suitable for conductor cross section of 1.0mm² (18AWG) ~ 4mm² (12AWG).

Wire Guard Mount



Accessory Mount








4 **Notice:**
Corrosion inhibiting grease, such as high and low temperature grease 7017-1B, may be applied to joint surfaces before assembly. It does not harden because of aging, does not contain evaporating solvent and does not cause corrosion of joint surfaces.

Grease (such as 7017-1B) (not provided)
Lamp post

Accessory Mount

Cone Top Unit: mm(inch)



This conical cover is an optional accessory that can be installed on top of the pendant to prevent dust accumulation. Please refer to "Pendant Mount" for detailed installation steps.

Safety Installation Guides

It's very important to cut off the power before removing the fixtures. Also, installer needs to be a qualified electrician. Remember, cut off power for at least 5 minutes then operate the removal.

• On-site installing

This manual is to provide the user with professional installation information, because the lamp is used in dangerous areas, so the qualified electrician is required.

• Use and setting-up

All wires need to be tested for proper connection and safe installation before use. In order to avoid the risk of electrical damage and installation safety problem, these jobs must be performed by a qualified electrician.

• Assembling and dismantling

Installer needs to read the instruction carefully before processing the assembling. Please feel free to contact the manufacturer if there is confusion during the installation.

• Training instructions for a safe use

Regards the wiring diagram please refers to installation detailed instruction below. Normally, brown (or black) wire connects to live wire, blue (or white) to nature wire, green with yellow (or green) strips to the grounding.


CAUTION: To Reduce The Risk Of Ignition Of Hazardous Atmospheres, Disconnect The Luminaire From The Supply Circuit Before Opening. Keep Tightly Closed When In Operation.

ATTENTION: Pour réduire le risque d'inflammation d'atmosphères dangereuses, débranchez le luminaire du circuit d'alimentation avant de l'ouvrir. Garder hermétiquement fermé lors de l'utilisation.


Wiring Diagram (One cable entry)

One cable gland

Ceiling Mount (1)




Ceiling Mount (2)




Pendant Mount




Trunnion Mount




Pendant & Trunnion Mount




Wall Bracket Mount




25°Stanchion Mount




30°Stanchion Mount




90°Stanchion Mount



Non-Dimmable



Dimmable




Emergency

Test switch with LED indicator:

Test switch: When the mains is connected, the emergency power module will work. If the test switch is pressed, the emergency power module will enter the emergency mode. If the switch is released, the lamp will enter the normal mains working mode, and the emergency power module will enter the charging mode.

LED indicator: LED indicator can indicate charging or non-charging status. When the battery is connected and there is mains power, the LED indicator lights up red, indicating that it is charging or fully charged; When the battery is not connected or there is no mains power supply or the emergency mode is working, the LED indicator is off.

NOTE: During normal operation, this switch is not used.




Stanchion Mount

Unit: mm(inch)


25° Stanchion Mount

Conduit entry (1pcs)
(Thread specification: 1-1/4"NPT OR 1-1/2"NPT)




30° Stanchion Mount

Conduit entry (1pcs)
(Thread specification: 1-1/4"NPT OR 1-1/2"NPT)




90° Stanchion Mount

Conduit entry (1pcs)
(Thread specification: 1-1/4"NPT OR 1-1/2"NPT)




1




Unscrew the A, B, C three screws on the power box counterclockwise

2




Pull up the three screws A, B, and C, and remove the power box downwards


3



1 Connect the ground wire to the hood




2 After securing the hood, close the power box




3 Tighten the three screws on the power box

4



Grease (such as 7017-1B) (not provided)

Lamp post











Hub locking screw.

The protection level of the Stanchion and the luminaire is above IP66

Wall Bracket Mount

Unit: mm(inch)


Conduit entry(4pcs)
(Thread specification: M25X1.5 OR M20X1.5
OR 3/4"NPT OR 1"NPT OR 1/2"NPT)



Note:

1. L1 (black wire) can be connected to a live switch (also called a normally closed switch). When this switch is turned off but there is mains power, the battery is still in charging mode, the indicator light will turn red, and when mains power is disconnected, the lamp will enter emergency mode.
2. When there is no need to connect the live switch, L1 (black wire) and L (brown wire) can be connected together.


Emergency + Dimmable




Note:

1. L1 (Live Switch) can be connected to a live wire switch (also called a normally-closed switch). When there is power, after turning off this switch (disconnect the live wire), the fixture would be off, but the battery is still in charging mode, and indicator would turn green. When the power is disconnected, the fixture would enter emergency mode.
2. When there is no need to connect the Live Switch, L1 (Live Switch) and L could be connected together.


Adjustment Power



Adjustable Power Module



Adjust the power by percentage by toggling the switch




Notice:


It is very important not to open the upper enclosure to adjust the power module while the luminaire is operating, powered on, or in an explosive gas environment.

Wiring Diagram (Two or more cable entry)


Ceiling Mount (1)




Ceiling Mount (2)




Pendant Mount




Trunnion Mount



Pendant & Trunnion Mount




Wall Bracket Mount




* The standard configuration includes two cable entries. If three cable entries are required, please specify this when placing order.

6



Pendant & Trunnion Mount




Notice:



1. Choose the appropriate cable and pay attention to the number of cores.
2. Choose the product that enters the line from the top or from the side according to the demand.
3. Wiring according to the wiring diagram.
4. Corrosion inhibiting grease, such as high and low temperature grease 7017-1B, may be applied to joint surfaces before assembly, it does not harden because of aging, does not contain evaporating solvent and does not cause corrosion of joint surfaces.
5. Shall use certified cable glands with suitable type of protection for installation purpose. Minimum IP66 for chosen cable glands.
6. Conduit entry should be blocked with plugs when not in use.

7


For Wall Mount or Ceiling Mount on cement surface: Drill two holes with 14 mm diameter on the mounting surface and spaced 126 mm apart. Using two M10-12 mm, length 80-120 mm expansion bolts with flat washer, spring washer and nut to fix the luminaire to the mounting surface. (Expansion bolts with flat washer, spring washer and nut are not provided)



Notice: For Class II and III installations only, luminaire mounting range is limited to lens down to horizontal.




Notice: For Class II and III installations only, luminaire mounting range is limited to lens down to horizontal.




Trunnion Mount

Unit: mm(inch)




1 Pendant & Trunnion Mount




When the product requires hanging installation, please rotate the U-shaped bracket 90 degrees to the side to fix it, and then refer to "Hanging Installation" for detailed installation steps

2 When the product requires trunnion mount




Unscrew the A, B, C three screws on the power box counterclockwise

3




Pull up the three screws A, B, and C, and remove the power box downwards


4




Using two M10-12 mm, length 60-120 mm expansion bolts with flat washer, spring washer and nut to fix the luminaire to the mounting surface. (Expansion bolts with flat washer, spring washer and nut are not provided)



5




Non-Dimmable



Note:
1. Inlets B, C and D can be used to interconnect lamps and need to be blocked with plugs when not in use.


Emergency + Dimmable




Note:
1. L1 (Live Switch) can be connected to a live wire switch (also called a normally-closed switch). When there is power, after turning off this switch (disconnect the live wire), the fixture would be off, but the battery is still in charging mode, and indicator would turn green. When the power is disconnected, the fixture would enter emergency mode.
2. When there is no need to connect the Live Switch, L1 (Live Switch) and L could be connected together.
3. CONDUIT HUB B, C and D can be used for Interconnect luminaire and should be blocked with plugs when not in use.

Ceiling Mount

Unit: mm(inch)



Conduit entry (2pcs *)
(Thread specification: M25X1.5 OR
M20X1.5 OR 3/4"NPT OR 1/2"NPT)



Conduit entry (2pcs *)
(Thread specification: M25X1.5 OR
M20X1.5 OR 3/4"NPT OR 1/2"NPT)

1

Unscrew the A, B, C three screws on the power box counterclockwise

2

Pull up the three screws A, B, and C, and remove the power box downwards

3

Expansion screws are first fixed on the ceiling surface

Recommended Expansion screws: M10X60 (not provided)

4

Connect the ground wire to the hood

4

Connect the ground wire to the hood

Notice:
Be careful not to pinch the ground wire when fixing the hood.

5

Hanging the fixture on the hood

1

After securing the hood, close the power box

2

Pull down the three screws A, B, and C downwards

3

Tighten the three screws on the power box

6

Ceiling Mount 2

4


The protection level of cable gland and cable, cable gland and the luminaire is above IP66

Notice:

- Choose the appropriate cable and pay attention to the number of cores.
- Choose the product that enters the line from the top or from the side according to the demand
- Wiring according to the wiring diagram.
- Corrosion inhibiting grease, such as high and low temperature grease 7017-1B, may be applied to joint surfaces before assembly. It does not harden because of aging, does not contain evaporating solvent and does not cause corrosion of joint surfaces.
- Shall use certified cable glands with suitable type of protection for installation purpose. Minimum IP66 for chosen cable glands.
- Conduit entry should be blocked with plugs when not in use.

Pendant Mount

Unit: mm(inch)



Conduit entry
(Thread specification: M25X1.5 OR M20X1.5
OR 3/4"NPT OR 1"NPT OR 1/2"NPT)

Conduit entry (2 * pcs)
M25X1.5 OR M20X1.5 OR
3/4"NPT OR 1/2"NPT

1

Unscrew the A, B, C three screws on the power box counterclockwise

2

Remove the screw

3

Connect the hood to the conduit stem

4

Tighten the screw

2

Connect the ground wire to the hood

Notice:
Be careful not to pinch the ground wire when fixing the hood.

3

Tighten the three screws on the power box

4

Hub locking screw (M4)
The protection level of the conduit stem and the luminaire is above IP66

Notice:

- Choose the appropriate cable and pay attention to the number of cores.
- Conduit entry matches cable size.
- Wiring according to the wiring diagram.
- Corrosion inhibiting grease, such as high and low temperature grease 7017-1B, may be applied to joint surfaces before assembly. It does not harden because of aging, does not contain evaporating solvent and does not cause corrosion of joint surfaces.
- Using certified cable glands with suitable type of protection for installation purpose. Minimum IP66 for chosen cable glands.
- Conduit entry should be blocked with plugs when not in use.